

# REEFER

		SPRING			NORMAL		
AXLE GROUP:		TANDEM (72")	TRIDEM (6'/6')	TOLERANCE	TANDEM (72")	TRIDEM (6'/6')	TOLERANCE
<b>NB</b>	STEERING	5500	5500	<i>None allowed</i>	5500	5500	<i>For each axle, add 500 kgs</i>
	TANDEM (60")	18000	18000	<i>Add'l route</i>	18000	18000	
	TRAILER	18000	26000	<i>reductions</i>	18000	26000	
	<b>TOTAL</b>	<b>41500 kg</b>	<b>49500 kg</b>	<i>are posted</i>	<b>41500 kg</b>	<b>49500 kg</b>	
<b>NS</b>	STEERING	5500	5500	<i>None allowed</i>	5500	5500	***
	TANDEM (60")	18000	18000	<i>Add'l route</i>	18000	18000	<b>NONE</b>
	TRAILER	18000	26000	<i>reductions</i>	18000	26000	<b>ALLOWED</b>
	<b>TOTAL</b>	<b>41500 kg</b>	<b>49500 kg</b>	<i>are posted</i>	<b>41500 kg</b>	<b>49500 kg</b>	***
<b>PE</b>	STEERING	5500	5500	<i>None allowed</i>	5500	5500	<i>For each axle, add 500 kgs</i>
	TANDEM (60")	18000	18000	<i>Add'l route</i>	18000	18000	
	TRAILER	18000	26000	<i>reductions</i>	18000	26000	
	<b>TOTAL</b>	<b>41500 kg</b>	<b>49500 kg</b>	<i>are posted</i>	<b>41500 kg</b>	<b>49500 kg</b>	
<b>QC</b>	STEERING	5500	5500	***	5500	5500	***
	TANDEM (60")	15500	15500	<b>NONE</b>	18000	18000	<b>NONE</b>
	TRAILER	15500	22000	<b>ALLOWED</b>	18000	26000	<b>ALLOWED</b>
	<b>TOTAL</b>	<b>36500 kg</b>	<b>43000 kg</b>	***	<b>41500 kg</b>	<b>49500 kg</b>	***
<b>ON</b>	STEERING	5500	5500	<i>None allowed</i>	5500	5500	***
	TANDEM (60")	1800	18000	<i>posted</i>	18000	18000	<b>NONE</b>
	TRAILER	1800	25500	<i>reductions</i>	18000	25500	<b>ALLOWED</b>
	<b>TOTAL</b>	<b>41500 kg</b>	<b>49000 kg</b>	<i>off 400 hwys"</i>	<b>41500 kg</b>	<b>49000 kg</b>	***
<b>MB</b>	STEERING	5500	5500	***	5500	5500	***
<b>SK</b>	TANDEM (60")	17000	17000	<b>NONE</b>	17000	17000	<b>NONE</b>
<b>AB</b>	TRAILER	17000	24000	<b>ALLOWED</b>	17000	24000	<b>ALLOWED</b>
<b>BC</b>	<b>TOTAL</b>	<b>39500 kg</b>	<b>46500 kg</b>	***	<b>39500 kg</b>	<b>46500 kg</b>	***